

# SAFETY DATA SHEET



## FLORIDA PAINTS

1900 TROPIFLEX: 100% Acrylic Elastomeric Wall Coating - White

### 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	ELASTOMERIC WALL COATING WHITE
<b>Product Code:</b>	1900
<b>Product Use:</b>	Paint


#### Manufacturer

FLORIDA PAINTS  
78 THIRD STREET  
WINTER GARDEN, FL 34787 | 407.986.1000

#### 24 Hour Emergency Telephone Number

CHEMTEL (US): (800)255-3924  
CHEMTEL (International): (813)248-0585

### 2. HAZARDS IDENTIFICATION

<b>Classification:</b>	This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) Carcinogenicity: Category 1A
<b>Signal Word:</b>	Danger
<b>Pictograms:</b>	
<b>Hazard Statements:</b>	H350: May cause cancer
<b>Prevention Precautionary Statements:</b>	P201: Obtain special instructions before use P202: Do not handle until all safety precautions have been read and understood P281: Use personal protective equipment as required
<b>Response Precautionary Statements:</b>	P308+313: IF exposed: Call a POISON CENTER or doctor/physician
<b>Storage Precautionary Statements:</b>	P405: Store locked up
<b>Disposal Precautionary Statements:</b>	P501: Dispose of contents/container to an approved waste disposal plant
<b>Hazards Not Otherwise Classified:</b>	None

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Weight %	CAS Number
Titanium dioxide	10% to 20%	13463-67-7
Calcium carbonate	10% to 20%	1317-65-3
Talc	1% to 5%	14807-96-6
Ethylene glycol	1% to 5%	107-21-1
Silicon dioxide	1% to 5%	7631-86-9
Texanol ester alcohol	0% to 1%	25265-77-4
Alumina trihydrate	0% to 1%	21645-51-2
Hydrous alumino silicate	0% to 1%	8031-18-3
Nonylphenol polyethylene glycol ether	0% to 1%	127087-87-0
Crystalline silica	0% to 1%	14808-60-7
Zirconium dioxide	0% to 1%	1314-23-4
Ammonium hydroxide	0% to 1%	1336-21-6
4,4-dimethyloxazolidine	0% to 1%	51200-87-4
Diethylene glycol	0% to 1%	111-46-6

### 4. FIRST AID MEASURES

<b>General Advice:</b>	No hazards requiring special first aid measures
<b>Eyes:</b>	Remove contact lenses, if applicable. Flush eyes with water for at least 10 minutes. Keep eyes wide open while flushing. Consult a physician if symptoms persist.
<b>Skin:</b>	Remove contaminated clothing. Flush affected area with soap and water. Consult a physician if irritation persists. Wash contaminated clothing before re-use.
<b>Ingestion:</b>	Remove dentures if applicable and wash out mouth with water. Drink large amounts of water. Consult a physician if symptoms persist.
<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration and consult a physician immediately. Consult a physician if symptoms persist.
<b>Most Important Symptoms/Effects:</b>	None known
<b>Notes to Physician:</b>	Treat symptomatically

### 5. FIRE FIGHTING MEASURES

<b>Suitable Extinguishing Media:</b>	Use measures suitable to the circumstances and environment
<b>Precautions for Firefighters:</b>	Wear self-contained breathing apparatus and protective gear
<b>Specific Hazards:</b>	Sealed containers may rupture if exposed to high temperatures

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions:</b>	Use proper personal protective equipment. Avoid contact with skin, eyes, and clothing. Avoid breathing vapors.
<b>Other Precautions:</b>	If safe to do so, prevent additional spillage
<b>Clean-Up Method:</b>	Soak up with non-combustible absorbent material. Dispose of used absorbent in suitable containers.

## 7. HANDLING AND STORAGE

<b>Handling Precautions:</b>	Avoid contact with skin, eyes, and clothing. Avoid breathing vapors, mists, or dust. Wear respiratory equipment if ventilation is insufficient.
<b>Storage Precautions:</b>	Keep container upright, properly labeled, tightly closed, and out of reach of children in a cool, dry, well-ventilated area.
<b>Incompatible Materials:</b>	None

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ammonium hydroxide(1336-21-6)		
ACGIH STEL:	35 ppm	--
ACGIH TWA:	25 ppm	--
NIOSH ST:	35 ppm	27 mg/m <sup>3</sup>
NIOSH TWA:	25 ppm	18 mg/m <sup>3</sup>
Calcium carbonate(1317-65-3)		
NIOSH TWA:	5 mg/m <sup>3</sup> (respirable fraction)	10 mg/m <sup>3</sup> (total dust)
OSHA PEL:	5 mg/m <sup>3</sup> (respirable fraction)	15 mg/m <sup>3</sup> (total dust)
Crystalline silica(14808-60-7)		
ACGIH TWA:	.025 mg/m <sup>3</sup>	--
NIOSH TWA:	.05 mg/m <sup>3</sup>	--
OSHA TWA:	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	250 mppcf/ %SiO <sub>2</sub> +5
Diethylene glycol(111-46-6)		
WEEL TWA:	10 mg/m <sup>3</sup>	--
Ethylene glycol(107-21-1)		
ACGIH C:	100 mg/m <sup>3</sup>	--
Silicon dioxide(7631-86-9)		
NIOSH TWA:	6 mg/m <sup>3</sup>	--
OSHA TWA:	20 mil particles/ft <sup>3</sup>	80 mg/m <sup>3</sup> / %SiO <sub>2</sub>
Talc(14807-96-6)		
ACGIH TWA:	2 mg/m <sup>3</sup>	--
NIOSH TWA:	2 mg/m <sup>3</sup>	--
OSHA TWA:	20 mppcf	--
Titanium dioxide(13463-67-7)		
TWA:	ACGIH: 10 mg/m <sup>3</sup>	OSHA: 15 mg/m <sup>3</sup>
Zirconium dioxide(1314-23-4)		
ACGIH:	TWA: 5 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup>
NIOSH:	TWA: 5 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup>
OSHA:	TWA: 5 mg/m <sup>3</sup>	--

<b>Engineering Measures:</b>	Maintain adequate ventilation to keep exposure to airborne contaminants at safe levels. Use explosion-proof equipment.
<b>Hygiene Measures:</b>	No eating, drinking, or smoking while in use. Avoid contact with skin, eyes, and clothing. Wash hands, forearms, and face after handling. Wash contaminated clothing before re-use.
<b>Eye/Face Protection:</b>	Safety glasses/goggles
<b>Skin Protection:</b>	Protective gloves and protective clothing
<b>Respiratory Protection:</b>	Respiratory equipment if ventilation is inadequate

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State:</b>	Liquid
<b>Color:</b>	Determined by customer (white by default)
<b>Odor:</b>	Little to none
<b>Odor Threshold:</b>	No information available
<b>pH:</b>	No information available
<b>Melting Point (°F):</b>	No information available
<b>Boiling Point (°F):</b>	100.0 -212
<b>Flash Point (°F):</b>	120.00
<b>Flash Point Method:</b>	Closed cup
<b>Evaporation Rate:</b>	No information available
<b>Flammability (Solid/Gas):</b>	No information available
<b>Flammability Limits:</b>	No information available
<b>Vapor Pressure (mm Hg):</b>	No information available
<b>Vapor Density:</b>	No information available
<b>Specific Gravity:</b>	No information available
<b>% Solubility in Water:</b>	No information available
<b>Octanol/Water Partition Coefficient:</b>	No information available
<b>Auto-Ignition Temperature (°F):</b>	No information available
<b>Decomposition Temperature (°F):</b>	No information available
<b>Viscosity (KU):</b>	115-118

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	Not applicable
<b>Possibility of Hazardous Reactions:</b>	None under normal conditions of use
<b>Hazardous Decomposition Products:</b>	None under normal conditions of use
<b>Stability:</b>	Stable under normal storage conditions
<b>Incompatible Materials:</b>	None
<b>Conditions to Avoid:</b>	Freezing

## 11. TOXICOLOGICAL INFORMATION

Alumina trihydrate(21645-51-2)	
Oral LD50 (rat):	>2000 mg/kg
Diethylene glycol(111-46-6)	
Dermal LD50 (rabbit):	11890 mg/kg
Oral LD50 (human):	1000 mg/kg
Oral LD50 (rat):	12565 mg/kg
Ethylene glycol(107-21-1)	
Dermal LD50 (rabbit):	10626 mg/kg
Oral LD50 (rat):	4700 mg/kg
Nonylphenol polyethylene glycol ether(127087-87-0)	
Dermal LD50 (rabbit):	2000-2991 mg/kg
Inhalation LC50 (rat, 4 hrs):	1.15 mg/L
Oral LD50 (rat):	960-3980 mg/kg
Silicon dioxide(7631-86-9)	
Oral LD50 (rat):	3160 mg/kg
Texanol ester alcohol(25265-77-4)	
Dermal LD50 (rabbit):	15200 mg/kg
Oral LD50 (rat):	6500 mg/kg
Titanium dioxide(13463-67-7)	
Dermal LD50 (rabbit):	>10000 mg/kg
Oral LD50 (rat):	>10000 mg/kg

<b>Primary Routes of Exposure:</b>	Eye contact, skin contact, inhalation
<b>Acute Toxicity:</b>	No information available

<b>Exposure Effects</b>	
<b>Eye Contact:</b>	Irritation
<b>Skin Contact:</b>	Irritation, drying
<b>Inhalation:</b>	Irritation of respiratory system
<b>Ingestion:</b>	Gastrointestinal irritation, diarrhea, nausea, vomiting
<b>Target Organ (Single Exposure):</b>	No information available
<b>Target Organ (Repeated Exposure):</b>	Prolonged or repeated exposure may cause organ damage and cancer
<b>Sensitization:</b>	No information available
<b>Carcinogenicity:</b>	No information available
<b>Mutagenicity:</b>	No information available
<b>Reproductive Toxicity:</b>	No information available
<b>Other:</b>	No information available

## 12. ECOLOGICAL INFORMATION

Alumina trihydrate(21645-51-2)	
Semi-static NOEC (salmo trutta, 96 hrs):	>0.07 mg/L
Static NOEC (algae, 72 hrs):	>0.004 mg/L
Static NOEC (water flea, 48 hrs):	>0.005 mg/L
Diethylene glycol(111-46-6)	
BCF:	100
Bioaccumulation (Leuciscus idus melanotus, 3 days):	0.05 mg/L
Biodegradability (anaerobic, 28 days):	90-100%

EC50 (water flea, 24 hrs):	>10000 mg/L
LC50 (fathead minnow, 96 hrs):	75200 mg/L
LC50 (goldfish, 24 hrs):	5000 mg/L
<b>Ethylene glycol(107-21-1)</b>	
EC50 (water flea, 24 hrs):	74000 mg/L
LC50 (golden orfe, 48 hrs):	>10000 mg/L
LC50 (rainbow trout, 96 hrs):	18500 mg/kg
LC50 (water flea, 48 hrs):	41000 mg/L
NOEC (fathead minnow, 7 days):	32000 mg/L
NOEC (fathead minnow, 96 hrs):	39140 mg/L
NOEC (water flea, 48 hrs):	24000 mg/L
<b>Nonylphenol polyethylene glycol ether(127087-87-0)</b>	
BCF:	5.9-48
Biodegradability:	<60%
EC50 (water flea, 48 hrs):	9.3-21.4 mg/L
IC50 (bacteria, 16 hrs):	>1000 mg/L
LC50 (fathead minnow, 96 hrs):	3.8-6.2 mg/L
<b>Texanol ester alcohol(25265-77-4)</b>	
Biodegradability (aerobic, 28 days):	>98%
Static EC50 (green algae, 72 hrs):	18.4 mg/L
Static EC50 (water flea, 48 hrs):	147.8 mg/L
Static LC50 (fathead minnow, 96 hrs):	33 mg/L
<b>Titanium dioxide(13463-67-7)</b>	
EC50 (water flea, 48 hrs):	>1000 mg/L
LC50 (fish, 96 hrs):	>1000 mg/L
<b>Zirconium dioxide(1314-23-4)</b>	
LC50 (zebrafish, 96 hrs):	>100 mg/L
Static EC50 (water flea, 48 hrs):	>100 mg/L

<b>Ecotoxicological Effects:</b>	The environmental impact of this substance has not been fully evaluated
<b>Persistence/ Degradability:</b>	No information available
<b>Bioaccumulative Potential:</b>	No information available
<b>Environmental Mobility:</b>	No information available
<b>Other Effects:</b>	No information available

### 13. DISPOSAL CONSIDERATIONS

<b>Disposal Method:</b>	Dispose of in accordance with federal, state, provincial, and local regulations.
-------------------------	--

### 14. TRANSPORT INFORMATION

<b>DOT:</b>	Not regulated
<b>ICAO/IATA:</b>	Not regulated
<b>IMDG/IMO:</b>	Not regulated

## 15. REGULATORY INFORMATION

<b>TSCA (US):</b>	All components are listed or exempt
<b>DSL (Canada):</b>	One or more components are listed on the NDSL. All others are listed or exempt.

<b><u>311/312 Hazard Categories</u></b>	
<b>Fire:</b>	No
<b>Pressure Generating:</b>	No
<b>Reactivity:</b>	No
<b>Acute:</b>	No
<b>Chronic:</b>	Yes

<b>SARA 313</b>			
<b>Chemical Name</b>	<b>CAS Number</b>	<b>Max Weight %</b>	<b>de minimis limit</b>
Ethylene glycol	107-21-1	5	1.0


<b><u>State Right-to-Know</u></b>						
<b>Chemical Name</b>	<b>CAS Number</b>	<b>MA</b>	<b>NJ</b>	<b>PA</b>	<b>RI</b>	
Titanium dioxide	13463-67-7	X	X	X	X	
Calcium carbonate	1317-65-3	X	X	X	X	
Talc	14807-96-6	X	X	X	X	
Ethylene glycol	107-21-1	X	X	X	X	
Silicon dioxide	7631-86-9	X	X	X		
Texanol ester alcohol	25265-77-4		X	X		
Alumina trihydrate	21645-51-2		X	X		
Hydrous alumino silicate	8031-18-3		X	X		
Nonylphenol polyethylene glycol ether	127087-87-0		X	X		
Crystalline silica	14808-60-7		X	X	X	
Zirconium dioxide	1314-23-4	X	X	X		
Ammonium hydroxide	1336-21-6	X	X	X		
4,4-dimethyloxazolidine	51200-87-4		X	X		
Diethylene glycol	111-46-6		X	X	X	

<b>California Proposition 65:</b>	This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm
-----------------------------------	---

## 16. OTHER INFORMATION

HMIS RATING	
Health:	1*
Flammability:	0
Reactivity:	0
Personal Protection:	--

### NFPA CODES



PPE rating has been left intentionally blank. Choose appropriate PPE based upon actual conditions of use.

<b>Revision Indicator:</b>	Revised 5/2/2018
<b>Disclaimer:</b>	The information contained in this Safety Data Sheet (SDS) is provided in good faith and is believed to be accurate as of the effective date listed. The information applies only to the product as provided and may not be valid if combined with other materials. No warranty is implied or given. The user is responsible for complying with all applicable laws and regulations.