



Printing date: 7/12/2017

Revision: 7/12/2017

### 1 Identification

- **Product identifier**
- **Trade name: 7740 Scott Thane WB Acrylic Urethane Water-Based Enamel Gloss**
- **Product code:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Paint
- **Restrictions on use:** Contact manufacturer/supplier
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Florida Paints & Coatings, LLC  
78 Third Street  
Winter Garden, FL 34787  
USA  
407-986-1000
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924, +1 (813)248-0585

### 2 Hazard(s) identification

- **Classification of the substance or mixture**  
The product is not classified as hazardous according to the Globally Harmonized System (GHS).

---

- **Label elements**
- **GHS label elements:** Not regulated.
- **Hazard pictograms:** Not regulated.
- **Signal word:** Not regulated.
- **Hazard statements:** Not regulated.
- **Precautionary statements:** Not regulated.


---

- **Other hazards**  
0 % of the mixture consists of component(s) of unknown toxicity.  
There are no other hazards not otherwise classified that have been identified.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

· **Components:**

13463-67-7	titanium dioxide	 Carc. 2, H351	<10%
57-55-6	propylene glycol		<5%

· **Additional information:**

Non-classification as a carcinogen is based on non-inhalable form of product. IARC listings for titanium dioxide note that the substance must be respirable.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

(Cont'd. on page 2)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 7/12/2017

Revision: 7/12/2017

**Trade name: 7740 SCOTT THANE WB ACRYLIC URETHANE WATER-BASED ENAMEL GLOSS**

For the wording of the listed Hazard Statements refer to section 16.

(Cont'd. of page 1)

#### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**  
Wash with soap and water.  
If skin irritation is experienced, consult a doctor.
- **After eye contact:**  
Remove contact lenses if worn, if possible.  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**  
Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; immediately call for medical help.
- **Most important symptoms and effects, both acute and delayed:**  
Slight irritant effect on eyes.  
Nausea in case of ingestion.  
May cause gastro-intestinal irritation if ingested.  
Diarrhea.
- **Indication of any immediate medical attention and special treatment needed:** Treat symptomatically.

#### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.
- **For safety reasons unsuitable extinguishing agents:** None.
- **Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation.  
Particular danger of slipping on leaked/spilled product.
- **Environmental precautions**  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Methods and material for containment and cleaning up**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Do not allow to dry out

(Cont'd. on page 3)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 7/12/2017

Revision: 7/12/2017

**Trade name: 7740 SCOTT THANE WB ACRYLIC URETHANE WATER-BASED ENAMEL GLOSS**

(Cont'd. of page 2)

Send for recovery or disposal in suitable receptacles.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**7 Handling and storage**

· **Handling**

· **Precautions for safe handling:**

Open and handle receptacle with care.

Use only in well ventilated areas.

Keep out of reach of children.

· **Information about protection against explosions and fires:**

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Do not store together with acids.

· **Further information about storage conditions:** Keep containers tightly sealed.

· **Specific end use(s)** No relevant information available.

**8 Exposure controls/personal protection**

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**13463-67-7 titanium dioxide**

PEL (USA)	Long-term value: 15* mg/m <sup>3</sup> *total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 10 mg/m <sup>3</sup> withdrawn from NIC
EL (Canada)	Long-term value: 10* 3** mg/m <sup>3</sup> *total dust;**respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m <sup>3</sup> total dust
LMPE (Mexico)	Long-term value: 10 mg/m <sup>3</sup> A4

**57-55-6 propylene glycol**

WEEL (USA)	Long-term value: 10 mg/m <sup>3</sup>
------------	---------------------------------------

(Cont'd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 7/12/2017

Revision: 7/12/2017

**Trade name: 7740 SCOTT THANE WB ACRYLIC URETHANE WATER-BASED ENAMEL GLOSS**

(Cont'd. of page 3)

EV (Canada)	Long-term value: 155* 10** mg/m <sup>3</sup> , 50* ppm *vapour and aerosol;**aerosol only
<b>1332-58-7 Kaolin</b>	
PEL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV (USA)	Long-term value: 2* mg/m <sup>3</sup> E; as respirable fraction
EL (Canada)	Long-term value: 2 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 2(D) mg/m <sup>3</sup> respirable
LMPE (Mexico)	Long-term value: 2* mg/m <sup>3</sup> A4, *fracción respirable

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid close or long term contact with the skin.

Avoid contact with the eyes.

· **Engineering controls:** No relevant information available.

· **Breathing equipment:**

Not required under normal conditions of use.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

· **Protection of hands:**

Gloves are advised for repeated or prolonged contact.

Wear protective gloves to handle contents of damaged or leaking units.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:**



Safety glasses

· **Body protection:** Not required under normal conditions of use.

· **Limitation and supervision of exposure into the environment**

Avoid release to the environment.

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **Appearance:**

**Form:** Liquid

(Cont'd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 7/12/2017

Revision: 7/12/2017

**Trade name: 7740 SCOTT THANE WB ACRYLIC URETHANE WATER-BASED ENAMEL GLOSS**

(Cont'd. of page 4)

· <b>Color:</b>	White
· <b>Odor:</b>	Mild
· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	8.5
· <b>Melting point/Melting range:</b>	Not determined.
· <b>Boiling point/Boiling range:</b>	253 °C (487 °F)
· <b>Flash point:</b>	117 °C (243 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Auto-ignition temperature:</b>	Not determined.
· <b>Decomposition temperature:</b>	Not determined.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Oxidizing properties:</b>	Non-oxidizing.
· <b>Vapor pressure:</b>	Not determined.
· <b>Density:</b>	
<b>Relative density:</b>	1.25
<b>Vapor density:</b>	Not determined.
<b>Evaporation rate:</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Soluble.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity</b>	
<b>Dynamic:</b>	6500 cPs
<b>Kinematic:</b>	Not determined.
<b>VOC content:</b>	150 g/L (less water)
· <b>Other information</b>	No relevant information available.

**10 Stability and reactivity**

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Reacts with oxidizing agents.  
Reacts with acids.
- **Conditions to avoid** Excessive heat.

(Cont'd. on page 6)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 7/12/2017

Revision: 7/12/2017

**Trade name: 7740 SCOTT THANE WB ACRYLIC URETHANE WATER-BASED ENAMEL GLOSS**

(Cont'd. of page 5)

- **Incompatible materials**  
Oxidizing agents  
Strong acids
- **Hazardous decomposition products**  
Possible in traces:  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NOx)

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eye:** Slight irritant effect on eyes.
- **Sensitization:** Based on available data, the classification criteria are not met.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer):**

13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide	3
14808-60-7	quartz	1

- **NTP (National Toxicology Program):**

Present in trace quantities.

14808-60-7	quartz	K
------------	--------	---

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

- **Probable route(s) of exposure:**

Ingestion.  
Eye contact.  
Skin contact.

- **Repeated dose toxicity:** No relevant information available.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:**  
Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

(Cont'd. on page 7)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 7/12/2017

Revision: 7/12/2017

**Trade name: 7740 SCOTT THANE WB ACRYLIC URETHANE WATER-BASED ENAMEL GLOSS**

(Cont'd. of page 6)

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Other adverse effects** No relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- |                                       |                 |
|---------------------------------------|-----------------|
| · <b>UN-Number</b>                    |                 |
| · DOT, ADR, IMDG, IATA                | Not regulated.  |
| · <b>UN proper shipping name</b>      |                 |
| · DOT, ADR, IMDG, IATA                | Not regulated.  |
| · <b>Transport hazard class(es)</b>   |                 |
| · DOT, ADR, IMDG, IATA                |                 |
| · <b>Class</b>                        | Not regulated.  |
| · <b>Packing group</b>                |                 |
| · DOT, ADR, IMDG, IATA                | Not regulated.  |
| · <b>Environmental hazards</b>        |                 |
| · <b>Marine pollutant:</b>            | No              |
| · <b>Special precautions for user</b> | Not applicable. |

(Cont'd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 7/12/2017

Revision: 7/12/2017

**Trade name: 7740 SCOTT THANE WB ACRYLIC URETHANE WATER-BASED ENAMEL GLOSS**

(Cont'd. of page 7)

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 304 (emergency release notification):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7	titanium dioxide
------------	------------------

14808-60-7	quartz
------------	--------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency):**

None of the ingredients are listed.

· **IARC (International Agency for Research on Cancer):**

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

13463-67-7	titanium dioxide	2B
------------	------------------	----

14808-60-7	quartz	1
------------	--------	---

(Cont'd. on page 9)



**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 7/12/2017

Revision: 7/12/2017

**Trade name: 7740 SCOTT THANE WB ACRYLIC URETHANE WATER-BASED ENAMEL GLOSS**

(Cont'd. of page 8)

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

13463-67-7 titanium dioxide

14808-60-7 quartz

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 11/29/2016 / -

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

LDLo: Lowest Lethal Dose Observed

Carc. 2: Carcinogenicity – Category 2

· **Sources**

Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))

Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do))

Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)