




## 1 Identification

- **Product identifier**
- **Trade name:** **8200 ULTRA EXTERIOR SUPERCOAT 100% ACRYLIC FLAT**
- **Product code:** 8200, 8201, 8203 \*FORMERLY 410W, 410T, 410A
- **Other means of identification:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Coating
- **Restrictions on use:** See Sections 8 and 10 for further information.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
Florida Paints  
78 3rd Avenue  
Winter Garden, FL 34787  
USA  
(407) 986-1000
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924, +1 (813)248-0585

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Carc. 2 H351 Suspected of causing cancer.

---

- **Label elements**
- **GHS label elements**  
Note for United States only:  
If a Category 2 carcinogen ingredient is present in the mixture at a concentration between 0.1% and 1%, information is required on the SDS for a product. However, a label warning is optional.  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**  
  
GHS08
- **Signal word:** Warning
- **Hazard statements:**  
H351 Suspected of causing cancer.
- **Precautionary statements:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves and eye protection.  
P308+P313 IF exposed or concerned: Get medical advice/attention.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Cont'd. on page 2)

**Trade name: 8200 ULTRA SUPERCOAT 100% ACRYLIC FLAT**

(Cont'd. of page 1)

- **Other hazards** There are no other hazards not otherwise classified that have been identified.

**3 Composition/information on ingredients**

- **Chemical characterization: Mixtures**

- **Components:**

13463-67-7	titanium dioxide	☠ Carc. 2, H351	<10%
1332-58-7	Kaolin		5%
57-55-6	Propylene Glycol		<5%

- **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.  
For the wording of the listed Hazard Statements refer to section 16.

**4 First-aid measures**

- **Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.  
If skin irritation is experienced, consult a doctor.

- **After eye contact:**

Remove contact lenses if worn.  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; immediately call for medical help.

- **Most important symptoms and effects, both acute and delayed:**

May cause gastro-intestinal irritation if ingested.  
Diarrhea.

- **Danger:** Suspected of causing cancer.

- **Indication of any immediate medical attention and special treatment needed:** Treat symptomatically.

**5 Fire-fighting measures**

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.

- **For safety reasons unsuitable extinguishing agents:** None.

- **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

(Cont'd. on page 3)

**Trade name: 8200 ULTRA SUPERCOAT 100% ACRYLIC FLAT**

(Cont'd. of page 2)

- **Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures:**  
Ensure adequate ventilation.  
Use personal protective equipment as required.
- **Environmental precautions:**  
Avoid release to the environment.  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections:**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling**
- **Precautions for safe handling:**  
Use only in well ventilated areas.  
Open and handle receptacle with care.  
Keep out of reach of children.
- **Information about protection against explosions and fires:**  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:**  
Store away from foodstuffs.  
Do not store together with acids.
- **Further information about storage conditions:** Keep containers tightly sealed.
- **Specific end use(s):** No relevant information available.

(Cont'd. on page 4)

**Trade name: 8200 ULTRA SUPERCOAT 100% ACRYLIC FLAT**

(Cont'd. of page 3)

**8 Exposure controls/personal protection**· **Control parameters**· **Components with limit values that require monitoring at the workplace:****13463-67-7 titanium dioxide**

PEL (USA)	Long-term value: 15* mg/m <sup>3</sup> *total dust
REL (USA)	See Pocket Guide App. A
TLV (USA)	Long-term value: 10 mg/m <sup>3</sup> withdrawn from NIC
EL (Canada)	Long-term value: 10* 3** mg/m <sup>3</sup> *total dust;**respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m <sup>3</sup> total dust
LMPE (Mexico)	Long-term value: 10 mg/m <sup>3</sup> A4

**1332-58-7 Kaolin**

PEL (USA)	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV (USA)	Long-term value: 2* mg/m <sup>3</sup> E; as respirable fraction
EL (Canada)	Long-term value: 2 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 2(D) mg/m <sup>3</sup> respirable
LMPE (Mexico)	Long-term value: 2* mg/m <sup>3</sup> A4, *fracción respirable

**57-55-6 Propylene Glycol**

WEEL (USA)	Long-term value: 10 mg/m <sup>3</sup>
EV (Canada)	Long-term value: 155* 10** mg/m <sup>3</sup> , 50* ppm *vapour and aerosol;**aerosol only

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

(Cont'd. on page 5)

**Trade name: 8200 ULTRA SUPERCOAT 100% ACRYLIC FLAT**

(Cont'd. of page 4)

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid close or long term contact with the skin.

Avoid contact with the eyes.

· **Engineering controls:** No relevant information available.· **Breathing equipment:**

Not required under normal conditions of use.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

· **Protection of hands:**

Wear protective gloves to handle contents of damaged or leaking units.

Gloves are advised for repeated or prolonged contact.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:** Follow relevant national guidelines concerning the use of protective eyewear.· **Body protection:** Protective work clothing· **Limitation and supervision of exposure into the environment**

Avoid release to the environment.

**9 Physical and chemical properties**· **Information on basic physical and chemical properties**· **Appearance:**· **Form:** Liquid· **Color:** White· **Odor:** Mild· **Odor threshold:** Not determined.· **pH-value:** 8.8· **Melting point/Melting range:** Not determined.· **Boiling point/Boiling range:** 255 °C (491 °F)· **Flash point:** 120 °C (248 °F)· **Flammability (solid, gaseous):** Not applicable.· **Auto-ignition temperature:** Not determined.· **Decomposition temperature:** Not determined.· **Danger of explosion:** Product does not present an explosion hazard.· **Explosion limits**· **Lower:** Not determined.· **Upper:** Not determined.· **Oxidizing properties:** Not determined.· **Vapor pressure:** Not determined.· **Density:**· **Relative density:** 1.34· **Vapor density:** Not determined.

(Cont'd. on page 6)



**Trade name: 8200 ULTRA SUPERCOAT 100% ACRYLIC FLAT**

(Cont'd. of page 5)

<b>Evaporation rate:</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Dispersible.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity</b>	
<b>Dynamic:</b>	6500 cPs
<b>Kinematic:</b>	Not determined.
<b>VOC content:</b>	100 g/L (Less water)
· <b>Other information</b>	No relevant information available.

**10 Stability and reactivity**

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions:** Reacts with strong acids.
- **Conditions to avoid:** Excessive heat.
- **Incompatible materials:** Strong acids
- **Hazardous decomposition products:**  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NOx)

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Based on available data, the classification criteria are not met.
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer):**

13463-67-7	titanium dioxide	2B
14808-60-7	quartz	1

- **NTP (National Toxicology Program):**  
Present in trace quantities.

14808-60-7	quartz	K
------------	--------	---

(Cont'd. on page 7)



**Trade name: 8200 ULTRA SUPERCOAT 100% ACRYLIC FLAT**

(Cont'd. of page 6)

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

- Ingestion.
- Inhalation.
- Eye contact.
- Skin contact.

· **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**

Carc. 2

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Suspected of causing cancer.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

**12 Ecological information**

· **Toxicity**

- **Aquatic toxicity** Harmful to aquatic life with long lasting effects.
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Other adverse effects:** No relevant information available.

**13 Disposal considerations**

· **Waste treatment methods**

· **Recommendation:**

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· **Uncleaned packagings**

· **Recommendation:** Disposal must be made according to official regulations.

(Cont'd. on page 8)



Trade name: 8200 ULTRA SUPERCOAT 100% ACRYLIC FLAT

(Cont'd. of page 7)

**14 Transport information**

· <b>UN-Number</b>	
· DOT, ADR, IMDG, IATA	Not regulated.
· <b>UN proper shipping name</b>	
· DOT, ADR, IMDG, IATA	Not regulated.
· <b>Transport hazard class(es)</b>	
· DOT, ADR, IMDG, IATA	
· Class	Not regulated.
· <b>Packing group</b>	
· DOT, ADR, IMDG, IATA	Not regulated.
· <b>Environmental hazards</b>	
· Marine pollutant:	No
· <b>Special precautions for user</b>	Not applicable.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 304 (emergency release notification):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**· **Chemicals known to cause cancer:**

13463-67-7	titanium dioxide
12174-11-7	Attapulgite (Palygorskite)
111-42-2	2,2'-iminodiethanol

(Cont'd. on page 9)



**Trade name: 8200 ULTRA SUPERCOAT 100% ACRYLIC FLAT**

(Cont'd. of page 8)

14808-60-7 | quartz

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

**· Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

**· Carcinogenic categories****· EPA (Environmental Protection Agency):**

None of the ingredients are listed.

**· IARC (International Agency for Research on Cancer):**

13463-67-7	titanium dioxide	2B
111-42-2	2,2'-iminodiethanol	2B
14808-60-7	quartz	1

**· NIOSH-Ca (National Institute for Occupational Safety and Health):**

13463-67-7	titanium dioxide
14808-60-7	quartz

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 09/30/2016 / -

**· Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 LDLo: Lowest Lethal Dose Observed  
 Acute Tox. 4: Acute toxicity – Category 4  
 Carc. 2: Carcinogenicity – Category 2  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

**· Sources**

Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))  
 Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do))  
 Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))  
 Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6  
 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

(Cont'd. on page 10)



**FLORIDA  
PAINTS**

**Safety Data Sheet**  
acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: 10/02/2019

Revision: 10/02/2019

**Trade name: 8200 ULTRA SUPERCOAT 100% ACRYLIC FLAT**

Safety Data Sheets, Individual Manufacturers

(Cont'd. of page 9)

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)