



Cirrus  
Low VOC Interior Latex Primer/Sealer  
Interior • Matte  
7560 Line

---

### Product Description

**Cirrus Low VOC Interior Latex Primer/Sealer** is specially formulated as an environmentally responsible premium quality interior primer/sealer that is low odor and contains low VOC's - (**Volatile Organic Compounds**). It also features a spatter resistant formula that promotes ease of application. It offers superior coverage, outstanding priming and sealing properties, and is ideally suited for application in occupied areas such as, Hospitals, Office Buildings, Government Buildings, Schools, Hotels/Motels, Nursing Homes, Schools, Apartments, etc., where low VOC coatings can benefit the health concerns of these types of environments.

---

### Recommended Substrates

#### Interior:

- gypsum drywall • plaster • ceilings • wall board
- masonry • concrete block • wood • acoustical ceilings

---

### Product Features

- Premium Acrylic Formula
- Low VOC
- Low Odor
- Spatter Resistant Formula
- Superior Coverage
- Primes & Seals
- Excellent Product Versatility
- Easy To Apply

### Product Data

<b>Product Type:</b>	Acrylic Latex
<b>Gloss @ 60°:</b>	Matte (0 – 5)
<b>Percent Solids:</b>	Weight: 56.11 ± 2% Volume: 40.21 ± 2%
<b>Spread Rate:</b>	350 SFPG
<b>Wet Film Thickness:</b>	4.6 Mils
<b>Dry Film Thickness:</b>	1.8 Mils
<b>VOC Content:</b>	< 50 g/l
<b>Viscosity:</b>	94 Krebs per unit ± 2
<b>Application:</b>	Brush, roller, or airless or conventional spray
<b>Dry Time: (@75°F &amp; 50% RH)</b>	To Touch: 30 min - 1 Hour To Recoat: 2 - 4 Hours

(Dry times listed may vary according to relative humidity, temperature, film build, color and air movement.)

<b>Flash Point:</b>	Nonflammable
<b>Clean Up:</b>	Warm soap and water
<b>Bases Available:</b>	White

---

### VOC Compliance

- AIM/EPA
- OTC
- LADCO
- CARB
- SCAQMD

---

### Performance

Complies with and meets performance criteria for specifications:

- N/A

---

### Product Limitations

This product is for use on properly prepared above grade vertical substrates. Do not apply to horizontal surfaces or areas that come in constant contact with standing water. Not for use in areas subject to intense heat, corrosive or chemical environments.

## Surface Preparation

**Caution!** There is the potential to release lead dust if you sand scrape or remove old paint. Lead is toxic and exposure to lead dust particles can cause serious illness including brain damage especially in children. Pregnant women should avoid exposure. If adequate ventilation is not possible, wear a NIOSH approved respirator to avoid inhalation of the fumes and wear clothing designed to prevent skin contact. Clean up carefully with a HEPA vacuum and a wet mop. Before starting your project, you can find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or visit their website at [www.epa.gov/lead](http://www.epa.gov/lead).

**General Surface Preparation:** The performance of this product is dependent on the integrity and soundness of the substrate. All surfaces should be clean and free of any dirt, rust, grease, mill oils, mill scale, efflorescence, organic growth, mildew or other contaminants that might adversely affect the adhesion and performance of this product. Any failed or deteriorated caulk or patching compound should be removed and replaced. Unpainted surfaces should be primed in accordance with manufacturer's recommendations. Glossy substrates should be de-glossed prior to painting.

Remove any loose, scaling, cracked or peeling paint from previously painted surfaces by hand scraping, sanding, wire brushing or by power tool cleaning methods, such as electric sanders or grinders, etc. For metal surfaces, remove any loose rust, mill scale, rust deposits or white rust from metal surface by the same methods as described above. Repair/replace any damaged and/or delaminated surface areas with the proper patching and/or building materials. Allow all patching materials to thoroughly dry before application of paint coatings. Sand all rough paint edges smooth to adjacent surface area. Sand all glossy surfaces to effectively dull existing finish.

Finish with any of **Florida Paints' Cirrus Low VOC Interior Latex Flat, Eggshell or Semi-Gloss** finish coatings.

**Mildew** - Surface areas affected by mildew should be treated with a commercial mildew removal and/or wash product carefully following manufacturer's application and safety directions. Rinse thoroughly with clean water, and allow a minimum of 24 hours to dry thoroughly.

## Directions For Use

**Application:** Stir thoroughly in a spiral up and down motion before and during application to keep product completely mixed. Use a quality nylon or polyester brush, or a 3/8" to 1 1/4" nap synthetic roller cover, or airless sprayer with a minimum pressure of 2000 PSI and a tip size between .017" and .019". During spray application, it may be necessary to back-roll the surface area to ensure proper adhesion, an even coat application, and to work primer coating into surface pores. Maintain a wet edge during application by brushing, rolling or spraying into previously applied coating area. Apply when surface and ambient temperatures are above 55° F and below 90° F.

**Dry Time / Cure:** Adverse weather conditions can negatively impact the performance of the product. Do not use when air, surface or product temperatures are below 50°F or above 100°F. Substrate temperature must be 5° above the dew point. Relative humidity should not exceed 85%. Cleaning should not occur until 30 days after the initial application.

**Clean Up:** Minor spills, painting tools and spray equipment should be immediately cleaned with soap and water. More serious spills should be contained and removed with inert absorbent material. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. **DO NOT THIN:** Stir thoroughly and apply as it comes from the container. Thinning is not necessary.

---

## Safety

CAUTIONS: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY! USE ONLY WITH ADEQUATE VENTILATION! Avoid prolonged contact with skin, and breathing of dust, vapors or spray mists. Avoid contact with eyes. Ensure fresh air entry during application and drying. Wear an appropriate fitted respirator (NIOSH approved.) Wear eye protection. Wash skin thoroughly after handling. Close container after each use and store in a secure, shaded and dry location. First Aid: In case of eye contact immediately flush with plenty of water for 15 minutes and get medical attention immediately. If swallowed do not induce vomiting and get medical attention immediately.

---

## Storage and Disposal

Product should be kept from freezing temperatures or temperatures above 95°F. Refer to your local city or county government for instructions on disposal options.

---

Florida Paints believes the technical data represented in this technical bulletin to be current and up to date. However, Florida Paints makes no warranties or guarantees either expressed or implied. Florida Paints claims no responsibility from damages incurred from use by either the purchaser or user of the product.

REV 12/13