

Interior Latex Drywall Texture Conditioner

Conditioner • 4350

Product Description

TexTight Interior Latex Drywall Texture Conditioner is a premium quality hardener/conditioner that improves the integrity of the finished texture on the wall surface. Because drywall texture alone does not contain a strong binder, the application of this product forms a substrate for the paint which will extremely improve the washability of the surface as well as touch up. **This product is for interior use only.**

Recommended Substrates <ul style="list-style-type: none"> • Drywall and GWB 	Available bases 4350: Translucent Application: Brush, roller, airless or conventional spray	Product Data Product Type: Waterborne Acrylic
Product Features <ul style="list-style-type: none"> • Hardens drywall texture • Improved durability • Great enamel holdout • Excellent adhesion • Non-yellowing • Quick drying and recoat • Soap and water clean up • Low odor 	Dry time @ 50% RH*: 1 HR to touch 4 HRS recoat <small>*dry times listed may vary according to the relative humidity, temperature, film build, color and air movement of the application environment</small> Flash Point: Non-Flammable >200°F Clean Up: Warm soapy water	Gloss @60°: 4350 N/A Wt Solids ±2%: 18% Vol Solids ±2%: 17% Wet Film Mils: 4.3 - 5.8 Dry Film Mils: 0.7 - 1.0 Coverage / Gal * 275 - 375 <small>* coverage and wet and dry millage will vary by substrate type and porosity.</small>
Product Limitations This product is for use on properly prepared above grade vertical substrates. Do not apply to horizontal surfaces or areas that come in constant contact with moisture or standing water.	Compliance This product is VOC compliant based on limits provided by EPA, CARB, MPI GSP-1 & GSP-2, LEEDv4, OTC and SCAQMD.	VOC gms p/L**: <50 <small>** less exempt solvents and before the addition of colorant</small> Viscosity KU ±5: 45

Surface Preparation

Caution! There is the potential to release lead dust if you sand scrape or remove old paint. Lead is toxic and exposure to lead dust particles can cause serious illness including brain damage especially in children. Pregnant women should avoid exposure. If adequate ventilation is not possible, wear a NIOSH approved respirator to avoid inhalation of the fumes and wear clothing designed to prevent skin contact. Clean up carefully with a HEPA vacuum and a wet mop. Before starting your project, you can find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or visit their website at www.epa.gov/lead.

General Surface Preparation: The performance of this product is dependent on the integrity and soundness of the substrate. All surfaces should be clean and free of any dirt, grease, efflorescence, organic growth, mildew or other contaminants that might adversely affect the adhesion and performance of this product. Any failed or deteriorated caulk or patching compound should be removed and replaced. Unpainted surfaces should be primed in accordance with manufacturer's recommendations. Glossy substrates should be deglossed prior to painting. **New Drywall:** Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust prior to priming.

Directions for Use

Application: May be easily applied with a quality brush, roller cover, or airless spray equipment. Stir thoroughly in a spiral up and down motion before and during application to keep product completely mixed. For best results, thin finish coats covering approximately 300-350 square feet gallon on smooth surfaces, less on more porous surfaces. During application, always paint to a natural break in the surface, such as a corner or edge. When applying by brush, apply a smooth and generous coat on smaller surface areas, such as cutting-in larger surfaces and painting trim. When applying by roller cover, apply an even and generous coat in a "W" or crisscross motion, avoiding any excessive respreading or reworking. Use a quality nylon or polyester brush, a 3/8" to 1/2" nap synthetic roller cover, or airless sprayer with a minimum pressure of 2000 PSI and a minimum .011" tip. Maintain a wet edge during application by brushing, rolling or spraying into previously applied coating area. Apply when surface and ambient temperatures are above 55° F and below 90° F.

Mixing: Stir thoroughly and apply as it comes from the container. Thinning is not necessary. **Clean Up:** Minor spills, painting tools and spray equipment should be immediately cleaned with soap and water. More serious spills should be contained and removed with inert absorbent material. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

Safety

CAUTIONS: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY! USE ONLY WITH ADEQUATE VENTILATION! Avoid prolonged contact with skin, and breathing of dust, vapors or spray mists. Avoid contact with eyes. Ensure fresh air entry during application and drying. Wear an appropriate fitted respirator (NIOSH approved.) Wear eye protection. Wash skin thoroughly after handling. Close container after each use and store in a secure, shaded and dry location. **First Aid:** In case of eye contact immediately flush with plenty of water for 15 minutes and get medical attention immediately. If swallowed do not induce vomiting and get medical attention immediately.

Storage and Disposal

Product should be kept from below 50°F or temperatures above 95°F. Refer to your local city or county government for instructions on disposal options.

Florida Paints believes the technical data represented in this technical bulletin to be current and up to date. However, Florida Paints makes no warranties or guarantees either expressed or implied. Florida Paints claims no responsibility from damages incurred from use by either the purchaser or user of the product.

PDS 4350 1811



Please excuse the small print used on this document but most paint company datasheets are two pages long. By squeezing all this information on one page we are doing our part to save a few trees.

Florida Paints and Coatings, LLC

78 3rd Street | Winter Garden, Florida 34787
407.293.4175 | info@FloridaPaints.com | FloridaPaints.com